



Kurz-Kasch, Inc.

Electronics Division
Box 1246 • 2271 Arbor Blvd.
Dayton, Ohio 45439
Telephone (513) 299-0990


Operating Instructions

For Model

#355A

PHOENIX/PLEIADES

CENTURI



1. Insert 355A program card into "A" connector on TF-650, number side up.
2. Connect 18/36 pin connector to GAME BOARD with RED DOT UP.
3. Connect a speaker across RED & BLACK pigtail leads coming from 18/36 pin connector.
4. Slide 5 VOLT switch to ON.
5. Slide POWER switch to ON.
6. Controls are:
 - COIN is CREDIT
 - START 1 is 1 PLAYER
 - START 2 is 2 PLAYER
 - SR1 is LEFT
 - SR3 is RIGHT
 - SR5 is FIRE
 - SR2 is SHIELD

PHOENIX ROM SIGNATURES

| LOCATION | TYPE | SIGNATURE | PERSONALITY BOARD |
|----------|--------|-----------|-------------------|
| IC-40 | MB7052 | TC12 | A16 |
| IC-41 | MB7052 | UA9P | A16 |
| IC-23 | 2716 | 056A | 2716/I24 |
| IC-24 | 2716 | 2C4P | 2716/I24 |
| IC-39 | 2716 | 7PFF | 2716/I24 |
| IC-40 | 2716 | F3F3 | 2716/I24 |
| IC-45 | 2716 | U91A | 2716/I24 |
| IC-46 | 2716 | 6515 | 2716/I24 |
| IC-47 | 2716 | 72FP | 2716/I24 |
| IC-48 | 2716 | 4H66 | 2716/I24 |
| IC-49 | 2716 | 85PC | 2716/I24 |
| IC-50 | 2716 | 0A2A | 2716/I24 |
| IC-51 | 2716 | 894H | 2716/I24 |
| IC-52 | 2716 | P844 | 2716/I24 |

(OVER)

ROM BOARD

| <u>LOCATION</u> | <u>MARKING</u> | <u>TYPE</u> | <u>SIGNATURE</u> | <u>PERSONALITY BOARD</u> |
|-----------------|----------------|-------------|------------------|--------------------------|
| IC-54 | R1 | 2716 | 3272 | 2716/I24 |
| IC-53 | R2 | 2716 | FCAF | 2716/I24 |
| IC-52 | R3 | 2716 | 3051 | 2716/I24 |
| IC-51 | R4 | 2716 | A0A8 | 2716/I24 |
| IC-50 | R5 | 2716 | 6802 | 2716/I24 |
| IC-49 | R6 | 2716 | F4CP | 2716/I24 |
| IC-48 | R7 | 2716 | P136 | 2716/I24 |
| IC-47 | R8 | 2716 | 932F | 2716/I24 |
| IC-45 | R11 | 2716 | AU25 | 2716/I24 |
| IC-44 | R12 | 2716 | 38C4 | 2716/I24 |
| IC-27 | R9 | 2716 | A534 | 2716/I24 |
| IC-26 | R10 | 2716 | U142 | 2716/I24 |

CPU BOARD

| | | | | |
|-------|---|----------|------|-----|
| IC-26 | A | M-7611-5 | 5P93 | A16 |
| IC-33 | B | M-7611-5 | H04A | A16 |