



Kurz-Kasch, Inc.

Electronics Division
 Box 1246
 2876 Culver Ave.
 Dayton, Ohio 45401
 Telephone (513) 296-0330

Operating Instructions For Model

224 A, B, C

NIGHT DRIVER

Atari

		SL2				START 2				SR2				5V
		x				x	x			x				
LLP	SL1	SL5	SL3	LAP		START 1	RLP	SR1	SR5	SR3	RRP	ON	OFF	
		x	x		x	x	x	x	x	x				
		SL4							SR4					
		x							x					
	SL8		SL7			COIN		SR6		SR7			POWER	
	x		x			x		x		x			ON	OFF

1. Insert 224 B card into program "B" connector, number side up.
2. Insert 224 A card into program "A" connector, number side up.
3. Insert 224 C card into TEST FIXTURE, with number side up.
4. Insert GAME BOARD into 224 C.
5. Connect a jumper wire from 5 VOLT jack on test fixture to end of 4 OHM, 10 WATT resistor near edgeboard connector. Also connect TEST FIXTURE ground strap to negative (-) end of 4700 MFD capacitor.
6. Push 5 VOLT switch to ON.
7. Push POWER switch to ON.
8. Push COIN switch once for COIN 1. LED will illuminate. Push SL7 switch once for COIN 2.
9. Push START 1 once. LED will extinguish.
10. Controls are:

1st - SR1	GAS - SR6	SL1 - Novice
2nd - SR2	SR5 - Car Right	SL3 - Expert
3rd - SR3	SL5 - Car Left	No buttons - Pro
11. SR7 is test pattern.
12. Connect 8 OHM speaker to RED and BLACK wires on 224 A card.