



Kurz-Kasch, Inc.

Electronics Division
 Box 1246
 1501 Webster Street
 Dayton, Ohio 45401
 Telephone (513) 223-8161

Operating Instructions For Model 275A, 270C

LAMP DRIVER

BALLY

		SL2				START 2				SR2			5V	
		x				x	x			x				
LLP	SL1	SL5	SL3	LAP		START 1	RLP		SR1	SR5	SR3	RRP	ON	OFF
x	x	x	x	x	x	x	x	x	x	x	x	x		
		SL4								SR4				
		x								x				
	SL6		SL7			COIN			SR6		SR7		POWER	
	x		x			x			x		x	x	ON	OFF

1. Insert the 270C card into the test fixture, number side up.
2. Insert the 275A card into the program A connector, number side up.
3. Connect the four cables from the 275A card to the Lamp Driver board.
4. Slide the 5 VOLT switch to "ON".
5. Slide the POWER switch to "ON".

NOTE: The 270C card provides a clock circuit and a 1 to 16 counter with BCD outputs to the four 1 of 16 decoders on the Lamp Driver board. Each 1 of 16 decoder is selected individually. The same outputs from each 1 of 16 decoders is or'ed together on the 275A card and turns on the proper L.E.D. on the 270C card.

6. Push START 2 to reset the clock and counter circuits.
7. Select the desired decoder by pushing:
 - SL-1 for U1
 - SL-2 for U2
 - SL-3 for U3
 - SL-4 for U4
8. Push COIN to advance the counter by one count. Holding the COIN button down will allow the count circuit to count at about 1 count per second.