



Kurz-Kasch, Inc.

Electronics Division
Box 1246 • 2271 Arbor Blvd.
Dayton, Ohio 45439
Telephone (513) 299-0990

Operating Instructions

For Model

303A

BALLY SOUNDBOARD

Bally Part No. AS-2888 series

		SL2				START 2			SR2				5V	
LLP	SL1	X	SL3	LRP	X	X	RLP	SR1	X	SR3	RRP		ON	OFF
		SL5				START1		SR5						
X	X	X	X	X	X	X	X	SR4	X		X			
		SL4												
	SL6	X	SL7			COIN		SR6	X	SR7			POWER	
	X		X			X		X		X	X		ON	OFF

1. Insert 303A card into program port "A"
2. Connect remote cable from 303A to J-1 on Soundboard.
Connect speaker (8 ohm to J-2 on Soundboard)
3. Turn on 5V DC.
4. Turn on Power (110V)
5. SL-1 Solenoid Address "A"
SL-2 Solenoid Address "B"
SL-3 Solenoid Address "C"
SL-4 Solenoid Address "D"
SL-5 Solenoid Address "E"
6. Push SL-1 - NOTE - Tone
Hold SL-1 & Push SL-5 - Tone should change.
7. Push SL-2 - NOTE - Tone
Hold SL-2 & Push SL-5 - Tone should change.
8. Push SL-3 - NOTE - Tone
Hold SL-3 & Push SL-5 - Tone should change.
9. Push SL-4 - Note - Tone
Hold SL-4 & Push SL-5 - Tone should change.
10. Use Bally repair procedures if Soundboard does not check as above.

WARNING: THIS CARD HAS 45V AC & DC on it. BE SURE REMOTE CABLE IS CONNECTED BEFORE TURNING ON FIXTURE.....





Kurz-Kasch, Inc.

Electronics Division
 Box 1246 • 2271 Arbor Blvd.
 Dayton, Ohio 45439
 Telephone (513) 299-0990

Operating Instructions

For Model


303A

BALLY SOUNDBOARD

		SL2			START 2			SR2			SV		
		X			X	X		X					
LLP	SL1	SL5	SL3	LRP		START1	RLP	SR1	SR5	SR3	RRP	ON	OFF
	X	X	X	X	X	X	X	X	X	X	X		
		SL4							SR4				
		X							X				
	SL6		SL7		COIN			SR6		SR7		POWER	
	X		X		X			X		X		ON	OFF

TO CHECK BOARD WITH "A" JUMPERS.....

1. Connect test clip from "B" jumper hole by base of Q-3 to base of Q-2.



2. Press SL-3---Tone should be heard.
3. Press SL-1 and SL-3---Lower tone should be heard.
4. Press SL-2 and SL-3---Lowest tone will be heard.
5. Press SL-1 and SL-2---Tone will be heard.