



**Kurz-Kasch, Inc.**

Electronics Division  
 Box 1246  
 2876 Culver Ave.  
 Dayton, Ohio 45401  
 Telephone (513) 296-0330

# Operating Instructions For Model 127 A

WHEELS

Midway/Bally

		SL2				START 2			SR2				5V
LLP	SL1	x	SL3	LRP	x	x	RLP	SR1	x	SR3	RRP	ON	OFF
		SL5				START 1			SR5				
x		x	x	x	x	x	x	x	x	x	x		
		SL4							SR4				
	SL6	x	SL7			COIN		SR6	x	SR7		POWER	
	x		x			x		x		x	x	ON	OFF

1. Insert card 127A into "A" connector, component side up.
2. Insert board to be tested into test fixture.
3. Attach lma meter positive terminal to T (tachometer) wire on card 127A, and GND.
4. Attach speaker between A (audio) wire and GND.
5. Turn power switch on.
6. Turn 5v switch on.
7. Push coin switch once (credit light will come on)
8. Push start switch once.
9. Set control RLP in center of range (accelerator)
10. Control RRP is steering.
11. Push SR6 to start car (gear shift), low gear button down, high gear button up.
12. Check WRN (warning), X play (extra play), and GO (game over lights).