



# Kurz-Kasch, Inc.

Electronics Division  
Box 1246 • 2271 Arbor Blvd.  
Dayton, Ohio 45439  
Telephone (513) 299-0990

## Operating Instructions

For Model 302C

Rock-ola Logic Unit

		SL2			START 2			SR2				5V	
LLP	SL1	x	SL3	LRP	x	x	RLP	SR1	x	SR3	RFP	ON	OFF
		SL5			START1				SR5				
x	x	x	x				x	x	x	x	x		
		SL4		x	x	x			SR4				
		x							x				
	SL6		SL7		COIN			SR6		SR7		POWER	
	x		x		x			x		x	x	ON	OFF

1. Plug in 300B into "B slot" on TF-650
2. Plug in 302C into "C slot" on TF-650
3. Connect 10 pin remote connector to P403 on Logic Board Dot up
4. Connect 12 pin remote connector to P401 on Logic Board Dot up
5. Slide switch on 302C toward "Home".
6. SW #1 away from edge of Logic Board.
7. 5V OFF & 110V Power-ON on TF-650 - 9.3V Led #1 on Logic Board must be ON.
8. a) Timer Led must FLASH  
b) OSC Led must be ON
9. Press Red & Blue (SW 2 & 3) ON Logic Board. Data & Clock Leds will be out
10. a) Move SW-1 on Logic toward edge of Logic Board  
b) Move Slide switch on 302C toward RUN
11. Data & Clock Leds will Pulse move slide switch on 302C to "Home"
12. PRESS RED (SW3) switch on Logic Board. Clock & Data Leds will cease pulsing.
13. Move Slide switch on 302C to RUN clock & Data Leds will resume pulsing.