



Kurz-Kasch, Inc.

Electronics Division
Box 1246 • 2271 Arbor Blvd.
Dayton, Ohio 45439
Telephone (513) 299-0990

Operating Instructions

For Model 406A
SUPER PAC MAN
MIDWAY

		SL2				START 2			SR2			5V	
		x				x	x		x				
LLP	SL1	SL5	SL3	LRP		START1	RLP	SR1	SR5	SR3	RRP	ON	OFF
	x	x	x					x	x	x			
x		SL4		x	x	x	x		SR4		x		
		x							x				
	SL6		SL7			COIN		SR6		SR7		POWER	
	x		x			x		x		x	x	ON	OFF

1. Insert 406A card into slot "A" number side up.
2. Connect 11-pin connector to circuit board, note the key position.
3. Connect 9-pin connector to circuit board, note the key position.
4. Connect 20-pin connector to circuit board, note key position.
5. Connect 10-pin connector to circuit board, note key position.
6. Turn 5V and power to ON position.
7. Controls are:

```

COIN-----COIN 1
SR6-----COIN 2
START 1----PLAYER 1 START
START 2----PLAYER 2 START
SR1-----MOVE LEFT
SR2-----MOVE UP
SR3-----MOVE RIGHT
SR4-----MOVE DOWN
SR5-----MOVE FAST WHEN SUPER PAC MAN
SL1-----MOVE LEFT
SL2-----MOVE UP
SL3-----MOVE RIGHT
SL4-----MOVE DOWN
SL5-----MOVE FAST WHEN SUPER PAC MAN
SL6-----TILT SWITCH
SL7-----SERVICE SWITCH
TEST SWITCH IS ON CARD,

```

2-player
cocktail mode

8. Connect speaker to short wires on 9-pin connector.

CPU BRD.

<u>POSITION</u>	<u>TYPE</u>	<u>SIGNATURE</u>	<u>PERSONALITY BOARD</u>
1B	2764-4	U175	Intel 2764
1C	"	CA34	"
1K	MBM2732A-35	23F1	2732/M24

VIDEO BOARD

3C	MBM2732A-35	OP18	2732/M24
3F	2764-4	CF2F	Intel 2764